

Recommended Product Gallery

UT60G

Modern Digital Multimeters



[Enlarge](#)



UL/cUL Pending

Registered Design No.: 0011438. 1M002

[Download Manual](#)

[Download Software](#)

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	600mV/6V/60V/600V/1000V	$\pm(0.5\%+3)$
AC Voltage	600mV/6V/60V/600V/1000V	$\pm(1\%+2)$
DC Current	60mA/600mA/10A	$\pm(1.2\%+3)$
AC Current	60mA/600mA/10A	$\pm(2\%+5)$
Resistance	600 Ω /6k Ω /60k Ω /600k Ω /6M Ω /60M Ω	$\pm(1\%+2)$
Capacitance	6nF/60nF/600nF/6 μ F/60 μ F/600 μ F/6mF	$\pm(4\%+3)$
Temperature ($^{\circ}$ C)	-40 $^{\circ}$ C ~ 1000 $^{\circ}$ C	$\pm(1\%+3)$
Frequency	6kHz/60kHz/600kHz/6MHz/60MHz	$\pm(0.05\%+3)$
Special Functions		
Fused 10A Range	✓	
Auto Ranging	✓	
Diode	✓	
Continuity Buzzer	✓	
Data Hold	✓	
RS232C	✓	
Display Backlight	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10M Ω	
Max. Display	5999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	63 x 31mm
Product Colour	Red and Grey
Product Net Weight	Around 312g
Product Size	177 x 73.5 x 35mm
Standard Accessories	Test Lead, Battery, English Manual, Point Contact Temperature Probe, Test Clip, RS232C Interface Cable, Software
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	595 x 400 x 326 mm (0.078 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 26kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)