

Recommended Product Gallery

UT50A

Modern Digital Multimeters



[Enlarge](#)



Registered Design No.: 0211977.6M003

[Download Manual](#)

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	$\pm (0.5\%+1)$
AC Voltage	200mV/2V/20V/200V/750V	$\pm (0.8\%+3)$
DC Current	20 μ A/2mA/200mA/20A	$\pm (0.8\%+1)$
AC Current	200 μ A/2mA/20mA/200mA/20A	$\pm (1\%+3)$
Resistance	200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /20M Ω /200M Ω	$\pm (0.8\%+1)$
Capacitance	2nF/20nF/2 μ F/100 μ F	$\pm (4\%+3)$
Special Functions		
Diode	✓	
Continuity Buzzer	✓	
Data Hold	✓	
Display Backlight	Auto Sensor	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10M Ω	
Max. Display	1999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	59 x 25mm
Product Colour	Red and Grey
Product Net Weight	Around 275g
Product Size	165 x 80 x 38.3mm
Standard Accessories	Test Lead, Battery, English Manual, Test Clip
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	Around 588 x 408 x 326 mm (Around 0.078 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 20kg

*Available at Extra Cost
Specifications and other information are subject to change without further notice.

[Back to main menu](#)